


High Pressure Thermocouples





INTRO TO HIGH PRESSURE THERMOCOUPLES



There are many considerations which must be taken into account, when designing thermocouples for high pressure service. The designer must be familiar with the effects of corrosion, environment, creep, fatigue, and thermal and mechanical stress.

Corrosion:

The designer must be aware of the possibility of corrosive conditions to make intelligent material choices. Material choices must be compatible with the process media over the entire operating temperature range of the device. This consideration is important to prevent production losses due to a premature failure of the high pressure devices.

Embrittlement:

Embrittlement occurs when metals exceed rated temperature or combine chemically with certain gases or other compounds. TCP engineers, in cooperation with the customer, carefully select the proper alloys to minimize or eliminate this problem.

Creep:

This condition is caused by high pressure and temperature. Careful attention is given to the possibility of metal deformation to hold it within prescribed limits. The design limits are particularly important when designing the sealing areas in high pressure service. Poor seals result in leaks with their associated safety record of their high pressure devices and thermocouple probes.

Fatigue:

Vibration, flexing, twisting etc. all are causes of fatigue failure. Fatigue failure is another problem our designers minimize by carefully questioning the customer and becoming familiar with the application. In this area, overdesign can be as harmful as underdesign in obtaining useful service life with maximum safety. Our design engineers have many years of successful experience in this important area.

Thermal Stress:

A critical area requiring a high degree of proficiency in the metallurgical sciences. Conditions caused by different coefficients of expansion in materials can cause problems at operating temperatures. These problems can become aggravated when subjected to overheating. Once again, these problems are handled routinely by TCP assuring you of a safe and accurate long lasting device.

Mechanical Stress:

Similar to thermal stress except mechanical stress failure is due to high pressures. Symptoms include bulges and ruptures. Successful design of devices to handle mechanical stress in addition to all the other conditions listed above is what sets TCP apart form the usual thermocouple supplier.


Manufacturing facilities at TCP include a machine shop, atmosphere brazing, controlled atmosphere heat treating facilities, heliarc and plazma are welding, hydrostatic pressure testing, radiographic equipment rated at 200 KV, metallurgical examination, and a complete testing and inspection program in accordance with ISO 9001:2000.





HIGH PRESSURE THERMOCOUPLE

Series 1500

- Temperature Sensing at Pressures Up to 60,000 PSI (PSI Rating Limited Only By High Pressure Fitting)
- 316 Stainless Steel Sheath Material and Support Tube Standard
- · Compacted MgO Insulation
- Grounded Junction (W2) Standard
- Industry Standard Color Coded Disconnect







CODE	SHEATH	A	В	C Thd	Mating Port Numbers		
	DIAMETER				Autoclave	H.I. P.	P.P.I.
С	.062"	.250"	.125"	9/16 - 18 NF	F250C	HF4	1/4 HP
D	.125"	.375"	.218"	3/4 - 16 NF	F375C	HF6	3/8 HP
E	.187"	.562"	.281"	1-1/8 - 12NF	F562C	HF9	9/16 HP

	uggested High Pressure Fitting Manufacturers
Autoclav	ve - Auto Engineers, Inc., Erie, PA.
H.I.P	- High Pressure Equipment Co., Inc., Erie, PA
P.P.I	- Pressure Products Industries, Hatboro, PA



Proprietary Brazing Process

On All High Pressure Thermocouples




a division of Marsh Bellofram www.marshbellofram.com 1-800-727-5646


HIGH PRESSURE THERMOCOUPLE

Series 1600

- Temperature Sensing at Pressures Up to 60,000 PSI (PSI Rating Limited Only By High Pressure Fitting)
- 316 Stainless Steel Sheath Material and Support Tube Standard
- · Compacted MgO Insulation
- Grounded Junction (W2) Standard
- Supplied with a Light Weight Screw-Cover Head








CODE	SHEATH	A	В	C Thd	Mating Port Numbers		
	DIAMETER				Autoclave	H.I. P.	P.P.I.
С	.062"	.250"	.125"	9/16 - 18 NF	F250C	HF4	1/4 HP
D	.125"	.375"	.218"	3/4 - 16 NF	F375C	HF6	3/8 HP
Е	.187"	.562"	.281"	1-1/8 - 12NF	F562C	HF9	9/16 HP

Suggested High Pressure Fitting Manufacturers				
Autoclav	re - Auto Engineers, Inc., Erie, PA.			
H.I.P	- High Pressure Equipment Co., Inc., Erie, PA			
P.P.I	- Pressure Products Industries, Hatboro, PA			



Proprietary Brazing Process

On All High Pressure Thermocouples